## **PRISMATICS**

GLAZED CERAMIC | WALL TILES

PLAIN COLOUR TILES SELECT












### **PRISMATICS**

With an unrivalled offering, our Prismatics collection is perfect for colourful installations with over 60 gloss and satin shades available, spanning the entire colour spectrum. A well-known, well-established range associated with high quality, Prismatics offers five different sizes, including a hexagon for even more striking designs. Ranging from vibrant, eye-catching colours, to neutral, warmer shades, Prismatics has it all. With colour graduated tonal profiles, it is easier for specifiers to identify complementary shades quickly and easily. Co-ordinated fittings are also available in selected colours to provide a complete finished look.

Front Cover Image: Teal Gloss 173x150mm Hexagon - PRG16













#### **Colours & Product Codes**

VI: Low Shade Variation















#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	200x200mm	G Gloss	All Colours Shown	6.5mm	25 Tiles	1.00 m²	11.50 kg
1	2008200111111	S Satin	All Colours Shown	6.5mm	25 Tiles	1.00 m <sup>2</sup>	11.50 kg
2	2 200x100mm	G Gloss	All Colours Shown	6.5mm	50 Tiles	1.00 m²	11.50 kg
2		S Satin	All Colours Shown	6.5mm	50 Tiles	1.00 m <sup>2</sup>	11.50 kg
3	150x150mm	G Gloss	All Colours Shown	6.5mm	44 Tiles	0.99 m²	11.50 kg
3	130x13011111	S Satin	All Colours Shown	6.5mm	44 Tiles	0.99 m²	11.50 kg
4	100x100mm	G Gloss	All Colours Shown	6.5mm	100 Tiles	1.00 m <sup>2</sup>	11.50 kg
4	100x100111111	S Satin	All Colours Shown	6.5mm	100 Tiles	1.00 m²	11.50 kg
5	173x150mm Hexagon	G Gloss	All Colours with 🕢	6.5mm	50 Tiles	0.98 m²	11.90 kg
J		S Satin	All Colours with 🕢	6.5mm	50 Tiles	0.98 m²	11.90 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. PG Price Group



#### Additional Fittings

VI: Low Shade Variation



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
	200x100mm	G Gloss	All Colours Shown	6.5mm	50 Tiles	10.00 lm	9.00 kg
'	REL	S Satin	All Colours Shown	6.5mm	50 Tiles	10.00 lm	9.00 kg
2	2 200×100mm	G Gloss	All Colours Shown	6.5mm	50 Tiles	5.00 lm	9.00 kg
	RES	S Satin	All Colours Shown	6.5mm	50 Tiles	5.00 lm	9.00 kg
3	200x100mm	G Gloss	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.08 kg
3	HREX	S Satin	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.08 kg
4	, 200×200mm	G Gloss	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.08 kg
4	REXH	S Satin	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.08 kg
5	200x100mm	G Gloss	All Colours Shown	6.5mm	45 Tiles	9.00 lm	9.00 kg
3	Cove	S Satin	All Colours Shown	6.5mm	45 Tiles	9.00 lm	9.00 kg
6	200x100mm	G Gloss	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.20 kg
6	Cove HRE	S Satin	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.20 kg
7	200x100mm	G Gloss	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.20 kg
/	Cove REH	S Satin	All Colours Shown	6.5mm	6 Tiles	1.20 lm	1.20 kg
8	200x25mm	G Gloss	All Colours Shown	6.5mm	20 Tiles	4.00 lm	1.20 kg
0	Int. Bead	S Satin	All Colours Shown	6.5mm	20 Tiles	4.00 lm	1.20 kg
9	200x25mm	G Gloss	All Colours Shown	6.5mm	20 Tiles	4.00 lm	1.20 kg
7	Ext. Bead	S Satin	All Colours Shown	6.5mm	20 Tiles	4.00 lm	1.20 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. PG Price Group



#### Technical Data

#### **Specification**

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Prismatics	All Sizes Shown	Internal Only	-	-	VI	Glazed Ceramic [BIII]

#### **Physical Properties**

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO I 0545 - 2	± 0.5% ≤ ± 2mm	≤ ± 0.25%	Modulus of Rupture EN ISO 10545 - 4	Min. I 5N / mm²	≥ 25N / mm²
<b>Thickness</b> EN ISO I 0545 - 2	± 10% ≤ ± 0.5mm	± 2.5%	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	± 0.15%	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A - B
Surface Flatness EN ISO I 0545 - 2	± 0.5% ≤ ± 2mm	± 0.3%	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class AI Non Combustible
kg Weight / M²	I I.50 kg 6.5mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

#### 

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD
Prismatics	Glazed Ceramic [BIII]	Up to 20%	Up to 100%	Up to 100%	Yes

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Prismatics pages on our website.

#### Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.

   The state of the sta
- $\bullet$  Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.







# For more information about Prismatics or any of our other product ranges simply visit www.johnson-tiles.com | f > 0 p in D

#### Where To Find Us

Johnson Tiles Harewood Street, Tunstall, Stoke on Trent,

Staffordshire,

ST6 5JZ

Tel: +44 (0) 1782 575 575 Fax: +44 (0) 1782 577 377 Email: info@johnson-tiles.com

#### Samples Enquiries

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379

 ${\bf Email: samples@johnson-tiles.com}$ 

#### Technical Helpline

Email: techadvice@johnson-tiles.com

